

# SHERCO

## 300 ST-F FACTORY

<b>Engine</b>	2 stroke
<b>Displacement</b>	294 cc (17.94 cu in)
<b>Bore x Stroke</b>	79 x 60 mm (3.11 x 2.36 in)
<b>Carburator</b>	Electronic injection
<b>Cooling</b>	Liquid system with forced circulation
<b>Starting</b>	Geared system with folding lever
<b>Exhaust</b>	Tubular section Chrome-moly
<b>Transmission</b>	5 speed sequential gearbox, primary gears and chain secondary
<b>Clutch</b>	Hydraulic, diaphragm system
<b>Électronic Ignition</b>	Hidria Digital
<b>Chassis</b>	Tubular section Chrome-moly
<b>Fuel Tank</b>	2.2 L (0.63 US Gal) capacity
<b>Brakes</b>	Hydraulically activation, floating Ø185 mm (7.28 in) front and Ø145 mm (5.71 in)
<b>Front suspension</b>	Aluminium Tech fork Ø 39 mm (1.54 in), 165 mm (6.50 in) travel
<b>Rear suspension</b>	REIGER
<b>Rear shock absorber</b>	Progression system with control linkage - 165 mm (6.49 in) stroke
<b>Front wheel</b>	Morad 21" Black rim
<b>Rear wheel</b>	Morad 18" Black rim
<b>Wheelbase</b>	1310 mm (51.57 in)
<b>Ground clearance</b>	350 mm (13.77 in)
<b>Seat base</b>	704 mm (27.71 in)

